














Modular I/O-System Overview

Fieldbus Couplers

Fieldbus System	Housing Design				Description	Item No.	Page
	with System Power Supply		without System Power Supply	ECO			
							
	<input type="checkbox"/>				Fieldbus Coupler, 100 Mbit	750-340	128
	<input type="checkbox"/>				Fieldbus Coupler, 2-port, 100 Mbit	750-370	130
		<input type="checkbox"/>			Fieldbus Coupler, advanced, 2-port	750-375	132
		<input type="checkbox"/>			Fieldbus Coupler, advanced, 2-port, extended operating temperature range: -20 °C ... +60 °C	750-375/025-000	132
			<input type="checkbox"/>		Fieldbus Coupler, advanced, ECO, 2-port	750-377	134
			<input type="checkbox"/>		Fieldbus Coupler, advanced, ECO, 2-port, extended operating temperature range: -20 °C ... +60 °C	750-377/025-000	134
	<input type="checkbox"/>				DP/FMS Fieldbus Coupler, 12 Mbaud	750-303	136
	<input type="checkbox"/>				DP/V1 Fieldbus Coupler, 12 Mbaud	750-333	138
	<input type="checkbox"/>				DP/V1 Fieldbus Coupler, 12 Mbaud, extended operating temperature range: -20 °C ... +60 °C	750-333/025-000	138
				<input type="checkbox"/>	DP/ECO Fieldbus Coupler, 12 Mbaud	750-343	140
	<input type="checkbox"/>				Fieldbus Coupler with Fiber Optic Plug, 1.5 Mbaud	750-331	142
			<input type="checkbox"/>		Fieldbus Coupler, 10/100 Mbit	750-352	144
MODBUS/TCP	<input type="checkbox"/>				Fieldbus Coupler, 10 Mbit	750-342	146
			<input type="checkbox"/>		Fieldbus Coupler, 100 Mbit/s	750-354	148
			<input type="checkbox"/>		Fieldbus Coupler, ID-Switch, 100 Mbit/s	750-354/000-001	150
	<input type="checkbox"/>				Fieldbus Coupler	750-306	152
				<input type="checkbox"/>	ECO Fieldbus Coupler	750-346	154
	<input type="checkbox"/>				Fieldbus Coupler	750-307	156
	<input type="checkbox"/>				Fieldbus Coupler	750-337	158
	<input type="checkbox"/>				Fieldbus Coupler, extended operating temperature range: -20 °C ... +60 °C	750-337/025-000	158
	<input type="checkbox"/>				Fieldbus Coupler, D-Sub	750-338	160
				<input type="checkbox"/>	ECO Fieldbus Coupler	750-347	162
				<input type="checkbox"/>	ECO Fieldbus Coupler, D-Sub	750-348	164
	<input type="checkbox"/>				Fieldbus Coupler, 2-port., 100 Mbit	750-351	166
MODBUS	<input type="checkbox"/>				Fieldbus Coupler, RS-485 (150 ... 115.2 kbaud)	750-315/300-000	168
	<input type="checkbox"/>				Fieldbus Coupler, RS-232 (150 ... 115.2 kbaud)	750-316/300-000	170
	<input type="checkbox"/>				Fieldbus Coupler, 500 kbaud	750-304	172
				<input type="checkbox"/>	ECO Fieldbus Coupler, 500 kbaud	750-344	174
				<input type="checkbox"/>	ECO Fieldbus Coupler, 2 Mbaud	750-345	176
	<input type="checkbox"/>				Fieldbus Coupler with Fiber Optic Plug	750-334	178
	<input type="checkbox"/>				Fieldbus Coupler	750-310	180