



VER.DATE: 19/04/2016

ΠΑΝΑΓΙΩΤΗΣ ΣΠ. ΔΗΜΟΥΛΑΣ – ΒΑΙΑ ΣΠ. ΔΗΜΟΥΛΑ Ε.Ε.
ΔΗΜΟΥΛΑΣ ΑΥΤΟΜΑΤΙΣΜΟΙ

ΣΥΣΤΗΜΑΤΑ ΜΕΤΡΗΣΕΩΝ ΚΑΙ ΑΥΤΟΜΑΤΙΣΜΟΥ

ΚΡΗΤΗΣ 26 – 10439 ΑΘΗΝΑ ΤΗΛ: 210 8833337 ΦΑΞ: 210 8834436

SITE: www.dimoulas.com.gr

ΤΙΜΟΚΑΤΑΛΟΓΟΣ ΚΛΕΜΜΕΣ ΕΛΑΤ. ΓΙΑ PCB WAGO

ΜΕ ΑΠΟΜΟΝΩΣΗ / ΜΕ ΑΣΦΑΛΕΙΑ / ΜΕ TEST POINTS (CAGE CLAMP)

ΤΑΞΙΝΟΜΗΣΗ ΑΝΑ ΚΩΔΙΚΟ

ΟΙ ΤΙΜΕΣ ΕΙΝΑΙ ΛΙΑΝΙΚΗΣ ΚΑΙ ΔΕΝ ΠΕΡΙΛΑΜΒΑΝΟΥΝ ΦΠΑ.

ΣΤΕΙΛΤΕ ΜΑΣ E-MAIL ΣΤΟ: sales@dimoulas.com.gr
με τα στοιχεία σας για την αποστολή της προσφοράς

ΣΗΜΕΙΩΣΗ:

Σε περίπτωση οποιασδήποτε διαφοροποίησης των περιγραφών από αυτές του κατασκευαστή, υπερισχύουν πάντα οι περιγραφές του κατασκευαστή

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
ΚΑΤΗΓΟΡΙΑ:	72,93 PCB ΚΛΕΜΜΕΣ ΕΛΑΤ. ΑΠΟΜΟΝΩΣΗΣ/ΤΕΣΤ/ΜΕ ΑΣΦΑΛΕΙΑ (cage clamp)			
742-100	End plate snap-fit type 1.5 mm thick, gray	0	300	0,11
742-101	Modular disconnect/test tb 2 solder pins/pole orange disconnect link, gray	0	384	1,4
742-106	Modular disconnect/test tb 2 solder pins/pole white disconnect link, orange	0	384	1,4
742-111	Modular fuse PCB terminal block gray	0	300	0,9
742-116	Modular fuse terminal block 2 solder pins/pole Pin spacing 5.08 mm / 0.2 in	0	300	0,9
742-121	Modular PCB terminal block 2 solder pins/pole Pin spacing 5 mm / 0.197 in, gray	0	300	0,59
742-124	Modular PCB terminal block 2 solder pins/pole Pin spacing 5 mm / 0.197 in, blue	0	300	0,64
742-126	Modular PCB terminal block 2 solder pins/pole Pin spacing 5.08 mm / 0.2 in, orange	0	300	0,59
742-128	Modular PCB terminal block 2 solder pins/pole Pin spacing 5 mm / 0.197 in, green-yellow	0	300	0,64
742-150	End plate snap-fit type 1.5 mm thick, gray	0	300	0,16
742-151	Modular 2-cond. disconnect/test tb 2 solder pins/pole orange disconnect link, gray	0	200	1,82
742-152	End plate snap-fit type 1.5 mm thick, gray	0	300	0,18
742-153	Modular 3-cond. disconnect/test tb 2 solder pins/pole orange disconnect link	0	100	2,23
742-156	Modular 2-cond. disconnect/test tb 2 solder pins/pole white disconnect link	0	200	1,82

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
742-158	Modular 3-cond. disconnect/test tb 2 solder pins/pole white disconnect link, orange	0	100	2,23
742-161	Modular 2-cond. fuse terminal block 2 solder pins/pole Pin spacing 5 mm / 0.197 in, gray	0	200	1,34
742-163	Modular 3-cond. fuse terminal block 2 solder pins/pole Pin spacing 5.08 mm / 0.2 in, gray	0	100	1,72
742-166	Modular 2-cond. fuse terminal block 2 solder pins/pole Pin spacing 5.08 mm / 0.2 in, orange	0	200	1,34
742-168	Modular 3-cond. fuse terminal block 2 solder pins/pole Pin spacing 5.08 mm / 0.2 in, orange	0	100	1,72
742-171	Modular 2-conductor terminal block 2 solder pins/pole Pin spacing 5 mm / 0.197 in, gray	0	200	1,04
742-174	Modular 2-conductor terminal block 2 solder pins/pole Pin spacing 5 mm / 0.197 in, blue	0	200	1,09
742-176	Modular 2-conductor terminal block 2 solder pins/pole Pin spacing 5.08 mm / 0.2 in, orange	0	200	1,04
742-178	Modular 2-conductor terminal block 2 solder pins/pole Pin spacing 5 mm / 0.197 in, green-yellow	0	200	1,09
742-400	End plate snap-fit type 1.5 mm thick, blue	0	300	0,12
742-408	Modular PCB terminal block	0	40	11,32
742-450	End plate snap-fit type 1.5 mm thick, blue	0	300	0,16
742-600	End plate snap-fit type 1.5 mm thick, orange	0	300	0,11
742-650	End plate snap-fit type 1.5 mm thick, orange	0	300	0,16
742-651	End plate snap-fit type 1.5 mm thick, orange	0	300	0,18
742-800	End plate snap-fit type 1.5 mm thick, green-yellow	0	300	0,11
742-850	End plate snap-fit type 1.5 mm thick, green-yellow	0	300	0,16