



VER.DATE: 19/04/2016

ΠΑΝΑΓΙΩΤΗΣ ΣΠ. ΔΗΜΟΥΛΑΣ – ΒΑΙΑ ΣΠ. ΔΗΜΟΥΛΑ Ε.Ε.
ΔΗΜΟΥΛΑΣ ΑΥΤΟΜΑΤΙΣΜΟΙ

ΣΥΣΤΗΜΑΤΑ ΜΕΤΡΗΣΕΩΝ ΚΑΙ ΑΥΤΟΜΑΤΙΣΜΟΥ

ΚΡΗΤΗΣ 26 – 10439 ΑΘΗΝΑ ΤΗΛ: 210 8833337 ΦΑΞ: 210 8834436

SITE: www.dimoulas.com.gr

ΤΙΜΟΚΑΤΑΛΟΓΟΣ ΒΥΣΜΑΤΑ ΤΥΠΩΜΕΝΟΥ Ή ΚΑΛΩΔΙΩΝ WAGO

MCS MAXI - 10 mm²

ΤΑΞΙΝΟΜΗΣΗ ΑΝΑ ΚΩΔΙΚΟ

ΟΙ ΤΙΜΕΣ ΕΙΝΑΙ ΛΙΑΝΙΚΗΣ ΚΑΙ ΔΕΝ ΠΕΡΙΛΑΜΒΑΝΟΥΝ ΦΠΑ.

ΣΤΕΙΛΤΕ ΜΑΣ E-MAIL ΣΤΟ: sales@dimoulas.com.gr
με τα στοιχεία σας για την αποστολή της προσφοράς

ΣΗΜΕΙΩΣΗ:

Σε περίπτωση οποιασδήποτε διαφοροποίησης των περιγραφών από αυτές του κατασκευαστή, υπερισχύουν πάντα οι περιγραφές του κατασκευαστή

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
ΚΑΤΗΓΟΡΙΑ:	72,4 ΒΥΣΜΑΤΑ MCS MAXI			
831-137	Adapter for DIN 35 rail snaps on CC-equipped male connectors, light gray		48	0,39
831-3025/000-004	Snap-on type strain relief housing Strain relief support and housing 5-pole		5	2,18
831-3102	MAXI FEMALE PLUG, PIN SPACING 7.62MM 10 MM ² , 2-P, LG-GREY 2-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	2,11
831-3102/000-9037	Female plug 2-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	2,34
831-3102/037-000	Female plug with locking levers 2-pole, light gray		24	2,51
831-3102/037-9035	FEDERL.CCS M.VK 7,62MM 2-POL. L-GRAU		24	
831-3102/037-9037	Female plug with locking levers 2-pole, light gray		24	2,72
831-3103	MAXI FEMALE PLUG, PIN SPACING 7.62MM 10 MM ² , 3-P, LG-GREY 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	3,2
831-3103/000-9036	Female plug 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	3,41
831-3103/000-9037	Female plug 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	3,41
831-3103/037-000	Female plug with locking levers 3-pole, light gray		24	3,58
831-3103/037-9035	FEDERL.CCS M.VK 7,62MM 3-POL. L-GRAU		24	
831-3103/037-9036	FEDERL.CCS M.VK 7,62MM 3-POL. L-GRAU		24	
831-3103/037-9037	Female plug with locking levers 3-pole, light gray		24	3,79

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
831-3104	Female plug 100% protected against mismating codable, light gray		24	4,28
831-3104/000-9035	Female plug 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,48
831-3104/000-9036	Female plug 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,51
831-3104/000-9037	Female plug 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,51
831-3104/037-000	Female plug with locking levers 4-pole, light gray		12	4,65
831-3104/037-9035	FEDERL.CCS M.VK 7,62MM 4-POL. L-GRAU		12	
831-3104/037-9036	FEDERL.CCS M.VK 7,62MM 4-POL. L-GRAU		12	
831-3104/037-9037	Female plug 100% protected against mismating codable, light gray		12	4,87
831-3105	Female plug 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,35
831-3105/000-9036	Female plug 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,57
831-3105/000-9037	Female plug 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,57
831-3105/037-000	Female plug with locking levers 5-pole, light gray		12	5,74
831-3105/037-9035	FEDERL.CCS M.VK 7,62MM 5-POL. L-GRAU		12	
831-3105/037-9036	FEDERL.CCS M.VK 7,62MM 5-POL. L-GRAU		12	
831-3105/037-9037	Female plug with locking levers 5-pole, light gray		12	5,96
831-3106	Female plug 6-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	6,42
831-3106/000-9037	Female plug 6-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	6,62
831-3106/037-000	Female plug with locking levers 6-pole, light gray		12	6,8
831-3106/037-9035	FEDERL.CCS M.VK 7,62MM 6-POL. L-GRAU		12	
831-3106/037-9037	Female plug with locking levers 6-pole, light gray		12	7,02
831-3107	Female plug 7-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	7,5
831-3107/000-9037	Female plug 7-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	7,72
831-3107/037-000	Female plug with locking levers 7-pole, light gray		12	7,87

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
831-3107/037-9035	FEDERL.CCS M.VK 7,62MM 7-POL. L-GRAU		12	
831-3107/037-9037	Female plug with locking levers 7-pole, light gray		12	8,09
831-3108	Female plug 8-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	8,56
831-3108/000-9037	Female plug 8-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	8,78
831-3108/037-000	Female plug with locking levers 8-pole, light gray		12	8,94
831-3108/037-9035	FEDERL.CCS M.VK 7,62MM 8-POL. L-GRAU		12	
831-3108/037-9037	Female plug light gray		12	9,16
831-3109	Female plug 9-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	9,64
831-3109/037-000	Female plug with locking levers 100% protected against mismatching, light gray		12	10,03
831-3202	MAXI MALE SOCKET, PIN SPACING 7.62MM 10 MM², 2-P, LG-GREY 2-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	2,31
831-3202/000-040	Male connector 2-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	2,37
831-3202/000-9032	Male connector 2-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	2,59
831-3202/000-9033	Male connector 2-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	2,59
831-3202/000-9034	Male connector 2-pole Pin spacing 7.62 mm / 0.3 in, light gray		48	2,52
831-3202/007-000	Male connector for DIN 35 rail mounting 2-pole, light gray		48	3,39
831-3202/007-040	Male connector for DIN 35 rail mounting 2-pole, light gray		48	3,45
831-3202/007-9032	Male connector for DIN 35 rail mounting 2-pole, light gray		48	3,67
831-3202/007-9033	Male connector for DIN 35 rail mounting 2-pole, light gray		48	3,67
831-3202/007-9034	Male connector for DIN 35 rail mounting 2-pole, light gray		48	3,6
831-3203	MAXI MALE SOCKET, PIN SPACING 7.62MM 10 MM², 3-P, LG-GREY 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	3,32
831-3203/000-040	Male connector 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	3,39
831-3203/000-9031	Male connector 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	3,6
831-3203/000-9032	Male connector 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	3,6

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
831-3203/000-9033	Male connector 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	3,6
831-3203/000-9034	Male connector 3-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	3,54
831-3203/007-000	Male connector for DIN 35 rail mounting 3-pole, light gray		48	4,39
831-3203/007-040	Male connector for DIN 35 rail mounting 3-pole, light gray		24	4,46
831-3203/007-9031	Male connector for DIN 35 rail mounting 3-pole, light gray		24	4,67
831-3203/007-9032	Male connector for DIN 35 rail mounting 3-pole, light gray		24	4,67
831-3203/007-9033	Male connector for DIN 35 rail mounting 3-pole, light gray		24	4,67
831-3203/007-9034	Male connector for DIN 35 rail mounting 3-pole, light gray		48	4,61
831-3204	Male connector 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,34
831-3204/000-040	Male connector 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,4
831-3204/000-9031	Male connector 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,62
831-3204/000-9032	Male connector 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,62
831-3204/000-9033	Male connector 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,62
831-3204/000-9034	Male connector 4-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	4,56
831-3204/007-000	Male connector for DIN 35 rail mounting 4-pole, light gray		24	5,44
831-3204/007-040	Male connector for DIN 35 rail mounting 4-pole, light gray		24	5,5
831-3204/007-9031	Male connector for DIN 35 rail mounting 4-pole, light gray		24	5,72
831-3204/007-9032	Male connector for DIN 35 rail mounting 4-pole, light gray		24	5,72
831-3204/007-9033	Male connector for DIN 35 rail mounting 4-pole, light gray		24	5,72
831-3204/007-9034	Male connector for DIN 35 rail mounting 4-pole, light gray		24	5,65
831-3205	Male connector 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,38
831-3205/000-040	Male connector 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,44
831-3205/000-9031	Male connector 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,65

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
831-3205/000-9032	Male connector 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,65
831-3205/000-9033	Male connector 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,65
831-3205/000-9034	Male connector 5-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	5,58
831-3205/007-000	Male connector for DIN 35 rail mounting 5-pole, light gray		24	6,45
831-3205/007-040	Male connector for DIN 35 rail mounting 5-pole, light gray		24	6,51
831-3205/007-9032	Male connector for DIN 35 rail mounting 5-pole, light gray		24	6,73
831-3205/007-9033	Male connector for DIN 35 rail mounting 5-pole, light gray		24	6,73
831-3205/007-9034	Male connector for DIN 35 rail mounting 5-pole, light gray		24	6,67
831-3206	Male connector 6-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	6,4
831-3206/000-040	Male connector 6-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	6,46
831-3206/000-9032	Male connector 6-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	6,68
831-3206/000-9033	Male connector 6-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	6,68
831-3206/000-9034	Male connector 6-pole Pin spacing 7.62 mm / 0.3 in, light gray		24	6,62
831-3206/007-000	Male connector for DIN 35 rail mounting 6-pole, light gray		24	7,48
831-3206/007-040	Male connector for DIN 35 rail mounting 6-pole, light gray		24	7,54
831-3206/007-9032	Male connector for DIN 35 rail mounting 6-pole, light gray		24	7,67
831-3206/007-9033	Male connector for DIN 35 rail mounting 6-pole, light gray		24	7,67
831-3206/007-9034	Male connector for DIN 35 rail mounting 6-pole, light gray		24	7,67
831-3207	Male connector 7-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	7,42
831-3207/000-040	Male connector 7-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	7,49
831-3207/000-9032	Male connector 7-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	7,7
831-3207/000-9033	Male connector 7-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	7,7
831-3207/000-9034	Male connector 7-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	7,63

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
831-3207/007-000	Male connector for DIN 35 rail mounting 7-pole, light gray		12	8,49
831-3207/007-040	Male connector for DIN 35 rail mounting 7-pole, light gray		12	8,56
831-3207/007-9033	Male connector for DIN 35 rail mounting 7-pole, light gray		12	8,77
831-3207/007-9034	Male connector for DIN 35 rail mounting 7-pole, light gray		12	8,71
831-3208	Male connector 8-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	8,44
831-3208/000-040	Male connector 8-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	8,5
831-3208/000-9032	Male connector 8-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	8,72
831-3208/000-9033	Male connector 8-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	8,72
831-3208/000-9034	Male connector 8-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	8,65
831-3208/007-000	Male connector for DIN 35 rail mounting 8-pole, light gray		12	9,52
831-3208/007-040	Male connector for DIN 35 rail mounting 8-pole, light gray		12	9,59
831-3208/007-9032	Male connector for DIN 35 rail mounting 8-pole, light gray		12	9,8
831-3208/007-9033	Male connector for DIN 35 rail mounting 8-pole, light gray		12	9,8
831-3208/007-9034	Male connector for DIN 35 rail mounting 8-pole, light gray		12	9,74
831-3209	Male connector 9-pole Pin spacing 7.62 mm / 0.3 in, light gray		12	9,46
831-3209/007-000	Male connector codable 100% protected against mismatching, light gray		12	10,56
831-3602	Male header (for PCBs) with straight solder pins 2-pole, light gray		48	1,25
831-3603	Male header (for PCBs) with straight solder pins 3-pole, light gray		48	1,83
831-3604	Male header (for PCBs) with straight solder pins 4-pole, light gray		24	2,42
831-3605	Male header (for PCBs) with straight solder pins 5-pole, light gray		24	3,01
831-3606	Male header (for PCBs) with straight solder pins 6-pole, light gray		24	3,61
831-3607	Male header (for PCBs) with straight solder pins 7-pole, light gray		12	4,19
831-3608	Male header (for PCBs) with straight solder pins 8-pole, light gray		12	4,8

ARTICLE NUMBER	DESCRIPTION_ENG	disc cat	PACK. UNIT	PRICE 1 PC
831-3622	Male header (for PCBs) with angled solder pins 2-pole, light gray		48	1,25
831-3623	Male header (for PCBs) with angled solder pins 3-pole, light gray		48	1,83
831-3624	Male header (for PCBs) with angled solder pins 4-pole, light gray		24	2,42
831-3625	Male header (for PCBs) with angled solder pins 5-pole, light gray		24	3,01
831-3626	Male header (for PCBs) with angled solder pins 6-pole, light gray		24	3,61
831-3627	Male header (for PCBs) with angled solder pins 7-pole, light gray		12	4,19
831-3628	Male header (for PCBs) with angled solder pins 8-pole, light gray		12	4,8
831-500	Coding pin carrier, six coding pins orange		100	0,48