

Thermal Transfer Printers

smartPRINTER

WAGO-smartPRINTER

The new thermal transfer printer from WAGO is especially compact and can handle a wide variety of different materials: marking strips, WMB Inline marker cards from rolls, labels, as well as conductor and wire markers.

Thus, it is possible to mark all WAGO terminal blocks as well as the connected conductors, cables, and label the devices using a single printer.

Item No. 258-5000

Roll mounting, cylinder, ink ribbon, 1 roll of marking strips, 1 roll of WMB Inline, 1 WAGO-ProServe® CD with installation information including a poster

WAGO Kontakttechnik GmbH & Co. KG
Postfach 28 80 · 32385 Minden
Hansastraße 27 · 32423 Minden

Phone +49/571/887-0
Fax +49/571/887-169

info@wago.com
www.wago.com

Available at the end of 2012
Our terms apply for delivery
and payment!





Description	Item no.	Pack. unit
smartPRINTER Thermal Transfer Printer	258-5000	1
Includes:		
smartSCRIPT Software		
Print cylinder for marking strips		
Print cylinder for WMB Inline, 5 mm		
Ink ribbon 57 mm x 74 running meters		
Marking strips	2009-110	1
WMB Inline	2009-115	1
Technical Data		
Printing method	Thermal transfer	
Print head	Glass layer, spring-mounted	
Print resolution	300 dpi (12 pixels/mm)	
Print speed	max. 127 mm/s (recommended 50.8 mm/s)	
Print width max.	47 mm	
Print length max.	762 mm	
Transmissive and reflective media sensor	yes, centrally fixed	
Working memory	8 MB flash memory, 16 MB SDRAM	
Ink ribbon	External roll diameter: 40 mm; internal core diameter 0.5" (12.7 mm); max length 110 m; max. width 58 mm	
Interfaces	USB, RS-232, ETHERNET 10/100 Mbps	
Accessories	External unwinder, power supply + cable, USB cable, 2 empty cardboard roller cores, installation poster	
Operating display	Color TFT-LCD with navigation buttons	
Operating voltage	Automatically adjusts from 100 to 240 A AC, 50-60 Hz	
Length	245 mm	
Height	175 mm	
Width	135 mm	
Weight	2000 g (without consumables)	
Operating temperature	5°C to 40°C (41°F to 104°F)	
Storage temperature	-20°C to 50°C (-4°F to 122°F)	
Certificate	UL	
Selected accessories		
Ink ribbon K500 for smartPRINTER	258-5005	1
Spare roller for markingSTRIP	258-5006	1
Spare roller for WMB Inline	258-5007	1
Marking strips, endless and self-adhesive, height 15 mm	210-702	1
Self-adhesive labels, 15 x 9 mm, white, 3000 units/roll	210-806	1
Self-adhesive labels, 20 x 8 mm, yellow, 3000 units/roll	210-807/000-002	1
Wire markers for threading on wires, writable surface 7 x 10.5 mm, wire cross section 2.5–6 mm²	211-862	1